

Cobra Globe 3100












Cobra's best seller over the last few years. Hundred of thousands of systems sold confirm the success of this modular range supplied and homologated all over the world, covering every need in vehicle security.

Available as part of a kit with high power backup battery siren or loudspeaker, it can also operate the original horn.

Key points: modular, universal application.



Kit incl. alarm unit with 2 push button remote control and high power siren

Installation time	  
Protection	   
Comfort	   

Siren power: > 115 dB (A)
Max. consumption: < 16 mA

Cobra Globe 3100

	AK3191
SYSTEM ARMING AND DISARMING	
High security remote controls with auto learning	x
5 button high security remote controls with auto-learning	
PROTECTION FUNCTIONS	
Single engine immobilisation circuit (built-in)	x
Immobiliser passive arming (P)	x
Alarm passive arming (P)	x
High power back up battery siren	
High power siren	x
Automatic re-arming in case of accidental disarming [P]	x
Additional output for siren/car horn [P]	
Panic alarm	x
Perimetric protection by contact (door, bonnet, boot)	x
Built-in pre-set ultrasonic volumetric protection [E]	x
Hyperfrequency volumetric sensor	(5462)
Level monitor	(5452)
Electronic emergency system (PIN code by Push button Max 4 digit)	x
Led indicator with diagnostic functions	x
Automatic door locking (vehicle speed sensor / time) [P]	x
Anti hi-jack (programmable in automatic and/or voluntary mode)	x
COMFORT FUNCTIONS	
Blinker (visual signalling for arm./disarm. and during the alarm)	x
Buzzer (acoustic signalling for arm./disarm.)	x
Universal central door locking system	6 wires
Controlled window closure by remote control for cars with original total closure	x
Controlled window closure module for cars without original total closure	(2980)
Door closure check	x
Exclusion of external optional sensors	x
Garage mode	x
Emergency disarm. through electronic key	

P= Programmable

E= Excludable

Technical features 3100:

Nominal voltage	12 VDC
Operating voltage range	9 - 16 VDC
Central unit temperature range	-40 °C - + 85°C
Siren temperature range	-40 °C - + 105°C
Central unit dimensions	61 x 30 x 73 mm
High power backup battery siren dimensions	76 x 76 x 67 mm
High power siren dimensions	65 x 75 x 35 mm